

EC Motors

A high quality, high efficiency replacement motor unit. Designed and developed in the UK and produced to ensure excellent reliability is key.

The original shaded pole motor would use 0.65KWh per day, but the new EC Motor consumes only 0.168KWh per day.



TECHNICAL DATA											
MODEL	VOLTAGE	FREQUENCY	INPUT	CURRENT	SPEED	AIR VOLUME	FAN BLADE	B	C	D	LICENSE
	V	Hz	W	A	r/min	m ³ /h	mm	mm	mm	mm	
GEC7108	220-240	50/60	3.0	0.028	1300	200	Ø154/28°	12	60	72	CE VDE
	110	50/60	2.6	0.046	1300	200	Ø154/28°	12	60	72	CE UL
	220-240	50/60	4.5	0.040	1300	300	Ø172/28°	12	60	72	CE VDE
	110	50/60	3.9	0.064	1300	300	Ø172/28°	12	60	72	CE UL
	220-240	50/60	4.8	0.041	1300	420	Ø200/31°	12	60	72	CE VDE
	110	50/60	4.5	0.068	1300	420	Ø200/31°	12	60	72	CE UL
GEC7112	220-240	50/60	7.5	0.065	1300	520	Ø200/34°	12	64	76	CE VDE
	110	50/60	7.0	0.103	1300	520	Ø200/34°	12	64	76	CE UL
	220-240	50/60	9.5	0.080	1300	710	Ø230/28°	12	64	76	CE VDE
	110	50/60	9.0	0.128	1300	710	Ø230/28°	12	64	76	CE UL
	220-240	50/60	10.5	0.090	1300	660	Ø254/22°	12	64	76	CE VDE
	110	50/60	15.8	0.163	1300	660	Ø254/22°	12	64	76	CE UL

